



144, 430/440, 1200 MHz ALL MODE TRANSCEIVER

IC-9700

- All mode, tri-band transceiver covering the 144, 430/440 as well as 1200 MHz
- New PA provides a powerful 100 W (144 MHz), 75 W (430/440 MHz) and 10 W (1200 MHz) output
- Follows Icom's center display design style with a 4.3 inch touch screen color TFT LCD
- Smooth satellite operation with normal/ reverse tracking and 99 satellite channels
- Real-time, high-speed spectrum scope for 144, 430/440, 1200 MHz bands
- Dualwatch operation and full-duplex operation in the satellite mode
- D-STAR provides digital clear audio and internet capable communication
- Digital Data (DD) mode provides 128 kbps data communication



Accessories

Hand Microphone (HM219) and DC power cable

Order Code	Description
IC-9700	144, 430/440, 1200 MHz ALL MODE TRANSCEIVER

Microphones

HM219	Hand Microphone with Up/Down Switches (AS SUPPLIED)
SM30	Compact, Lightweight electret desktop microphone
SM50	Dynamic Desktop Microphone including (Up/ Down) Switches and a low cut function

Power Supply

PS126	DC power supply (13.8 V DC, 25 A maximum output)
-------	--

IP Remote Control Software

RS-BA1	IP Remote Control Software (Version 2)
RS-MS1A	Remote Control application for Android™ and Google Play™

Mounting Bracket

MB118	Mobile Mounting Bracket
-------	-------------------------

Carry Handle

MB123	Carry Handle
-------	--------------

External Speaker

SP35	5w external speaker, 4 ohm, tweeter
SP38	High quality audio and matching height Maximum input: 7W
SP41	External Speaker with two input lines

Data Cable & programming software

CS9700	Programming Software
OPC-2350LU	PC/ Android™ Data cable